MATERIAL SAFETY DATA SHEET

1. Identification of the material and supplier Product name AL-2 Airbrush Lube Product use Airbrush Lubricant Supplier Paasche Airbrush Co 4311 N Normandy Ave Chicago, IL 60634 HMIS: HEALTH=1 Emergency FIRE=1 REACTIVITY=0 Phone : 1-800-621-1907 SPECIAL= NONE Infotrac

2. Hazards identification

Potential Health Effects

INHALATION: Negligible unless heated to produce vapors. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.

EYE CONTACT: May cause irritation. Irrigate eye with water for at least 15 to 20 minutes. Seek medical attention if symptoms persist.

SKIN CONTACT: Prolonged or repeated contact is not likely to cause significant skin irritation. Material is sometimes encountered at elevated temperatures. Thermal burns are possible.

INGESTION: No hazards anticipated from ingestion incidental to industrial exposure.

3. Composition/ information on ingredients OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200): Non-hazardous

4. First-aid measures			
Eye contact	In case of contact with eyes, rinse immediately with a copious amount of water.		
	Get medie	cal attention if irritation occurs.	
Skin contact		osed skin with soap and water. Remove contaminated clothing and	
	shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.		
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.		
Ingestion	If swallowed, DO NOT induce vomiting. Give several glasses of water to drink.		
	Never give anything by mouth to an unconscious person. Obtain medical		
	attention.		
5. Fire-fighting measures			
Flash point		> 275°C (COC)	
Extinguishing media		Carbon dioxide, dry chemical	
Protection of fire-fighters		Fire-fighters should wear self-contained positive pressure breathing	
		apparatus (SCBA) and full turnout gear.	
6. Accidental release measures			
Methods and materials for		SPILL CLEAN-UP PROCEDURES: Remove sources of ignition,	
containment and cleanup		contain spill to smallest area possible. Stop leak if possible. Pick up	
		small spills with absorbent materials such as paper towels, "Oil Dry",	
		sand or dirt. Recover large spills for salvage or disposal. Wash hard	
		surfaces with safety solvent or detergent to remove remaining oil film.	
		Greasy nature will result in a slippery surface.	
7 1 1 1	1 .		

7. Handling and storage

Store in closed containers between 50°F and 120°F. Keep away from oxidizing agents, excessive heat, and ignition sources. Store and use in well ventilated areas. Do not store or use near heat, spark, or flame; store out of sun. Do not puncture, drag, or slide this container. Drum is not a pressure vessel; never use pressure to empty.

8. Exposure controls/personal protection

EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m₃ is suggested for oil mist.

RESPIRATORY PROTECTION: If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.

PROTECTIVE CLOTHING: Safety glasses, goggles, or face shield recommended to protect eyes from mists or splashing. PVC coated gloves recommended to prevent skin contact.

OTHER PROTECTIVE MEASURES: Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before re-use.

9. Physical and chemical properties			
Physical state	Liquid		
Color	Clear yellow		
Boiling point	> 200°C		
Density	7.67lbs/gallon		
Solubility in water	Negligible		
10. Stability and reactivity			
Stability	Stable under normal conditions		
Incompatibility with various substances/	Avoid contact with strong oxidants.		
hazardous reactions	-		
Hazardous polymerization	Will not occur		
	Avoid excessive heat, formation of vapors or mists.		

11. Toxicological information

Routes of Exposure: Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mists.

Irritancy: Testing completed with this product or with one of similar formulation, indicates that the product is not a primary irritant and is not a skin sensitizer.

Chronic Effects: Long term intensive exposure to oil mist may cause benign lung fibrosis.

Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Used engine oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on actual conditions but the impurities may present risks to health or the environment on disposal. It is possible that prolonged or repeated exposure to used engine oils may cause skin cancer in humans. All used oils should be handled with caution and skin contact avoided as much as possible.

12. Ecological information

Environmental Effects:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.

Biodegradability: Readily biodegradable

13. Disposal information

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. Energy recovery (cement kilns, thermal power generation), 3. Incineration, 4. Disposal at a licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environmental authority. Landfill absorbed material in a government approved site.

14. Transport information

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

15. Regulatory information

OSHA STATUS: This product is not hazardous under the criteria of the Federal OSHA hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes from this product may be hazardous as noted in Section 3.

TSCA STATUS: The components of this product are listed on TSCA. CERCLA (Comprehensive Response Compensation, and Liability Act): Not reportable.

16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other tan for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Paasche Airbrush Co shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.